

# Fuel Oil (Mazut)

Catalog 2020



## Bandar Mahshahr (Abadan) 280CST Fuel Oil - Normal Export Quality

TEST	UNIT	SPECIFICATION	TEST METHOD
Density @ 15DC	KG/M3	MAX 970	D-1298
Kinematic Viscosity @ 50 Dc	Cst	Max 280	D-445
Visco.Rodwood1@37.7dc	Secs	Max 2500	CALCULATED
Pour Point	Dc	Max 24	D-97
Flash Point	Dc	Min 65	D-93
Sulfur Total	Wt%	Max 3.5	D-1552
Carbon Residue (Conradson) WT%	WT%	MAX 15	D-189
Ash	WT%	MAX 0.05	D-482
Water & Sediment	Vol%	Max 0.5	D-1796
Calorific Value (Higher)	Mj/Kg	Min 41.8	CALCULATED

## Bandar Abbas 380CST Fuel Oil - Normal Export Quality

TEST	UNIT	SPECIFICATION	TEST METHOD
Density @ 15DC	KG/M3	MAX 990	D-1298
Kinematic Viscosity @ 50 DC	CST	MAX 380	D-445
Pour Point	DC	MAX 32	D-97
Flash Point	DC	MIN 65	D-93
Sulfur Total	WT%	MAX 3.5	D-1552
Carbon residue (Conradson) WT%	WT%	MAX 15	D-189
Ash	WT%	MAX 0.15	D-482
Water & Sediment	VOL%	MAX 1.0	D-1796
Calorific Value (Higher)	MJ/KG	MIN 41.7	CALCULATED

---

Middle East Office:  
Unit B7, No. 62, Nelson  
Mandela Blvd., Tehran, Islamic  
Republic of Iran.

---

Tel: +9821-2842 1282  
info@raymondenergy.com  
www.raymondenergy.com

---

East Asia Office:  
Junyao International Plaza,  
No. 789, Zhaajiang Road,  
Shanghai, P.R. China.

---

CIS Office:  
No.136 ,2B, Novatorskaya  
St., 220053, Minsk, Belarus.

